



## 1-5/8" EIA Female Connector for 1-1/8" Coaxial Cable, Gas barrier, Sealing compound

Radio Frequency Systems line of high performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to HELIFLEX® coaxial cables. RFS connectors are fully tested for mechanical and electrical compliance specifications. They are available in all popular cable sizes in a variety of mating interfaces. To join two cables with EIA connectors, two identical socket connectors are installed on either end of the cables to be joined, and a coupling element is used to make the connection of the center conductor. The coupling element must be ordered separately with the exception of the S-Line male versions that have a captivated coupling element. Connectors are available in sizes matching the nominal cable size. EIA connectors provide optimal power handling for the complete transmission line system.;

Connector EIA 1 5/8"

### FEATURES / BENEFITS

- Excellent gas tightness, Overpressure for increased voltage handling is maintained throughout the system
- Robust Mechanical Design, Superior and consistent performance guarantees outstanding system characteristics.
- Extremely low reflection factor, Outstanding low reflection factor improves overall system performance and margin and reduces mismatch losses
- Totally Waterproof according to IP 68, Assures safe, long term operation in the harshest of environments. System tightness doesn't have to rely on overpressure from dehydration equipment.

### Technical Features

#### GENERAL SPECIFICATIONS

Transmission Line Type		Coaxial Cable
Cable Size		1-1/8"
Cable Type		Air Dielectric
Model Series		HCA118-50 Series
Connector Interface		1-5/8" EIA
Connector Type		Gas barrier
Sealing Method		Sealing compound <sup>1)</sup>
Gender		None

#### MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Silver/Silver
Length	mm (in)	128 (5.04)
Outer Diameter	mm (in)	59 (2.32)
Weight	kg (lb)	1.75 (3.86)
Inner Contact Attachment		Plug Finger
Outer Contact Attachment		Tab Flare

#### TESTING AND ENVIRONMENTAL

Sealing Volume	cm <sup>3</sup> (ounces)	10 (0.34)
----------------	--------------------------	-----------

### External Document Links

### Notes

<sup>1)</sup> The sealing compound must be ordered separately.