

1/2" RADIAFLEX® ALFU Cable, A-series

Product Description

RADIAFLEX® functions as a distributed antenna to provide communications in tunnels, mines and large building complexes and is the solution for any application in confined areas.

Slots in the copper outer conductor allow a controlled portion of the internal RF energy to be radiated into the surrounding environment. Conversely, a signal transmitted near the cable will couple into the slots and be carried along the cable length.

RADIAFLEX® is used for both one-way and two-way communication systems and because of its broadband capability, a single radiating cable can handle multiple communication systems simultaneously.

This RADIAFLEX® radiating cable utilize a low-loss cellular polyethylene foam dielectric and a smooth copper outer conductor which offers a superior electrical performance together with good bending properties.

Features/Benefits

- Ultra wideband from 30 MHz to 2650 MHz
- Heavy duty multiuse, for tunnel applications of all kind
- Easy system planning
- Insensitive to environmental influences < p

Technical Specifications

Size:	[in]	1/2"
Max. operating frequency:	[MHz]	2700
Cable Type:		ALF, RLF
Jacket	JFN	
Jacket Discription	Halogen free, non corrosive, flame and fire retardant, low smoke, polyolefin Test methods for fire behaviour of cable : IEC 60754-1/-2 smoke emission: halogen free, non corrosive IEC 61034 low smoke IEC 60332-1 flame retardant IEC 60332-3-24 fire retardant UL1666, ASTM E 662, NES711 and NES713	
Slot Design	Groups of slots at large intervals	
Impedance	[Ω]	50 +/-2
Relative propagation velocity	[%]	88
Capacitance	[pF/m (pF/ft)]	76 (23.2)
Inductance	[μH/m (μH/ft)]	0.190 (0.058)
DC-resistance inner conductor	[Ω/km (Ω/1000ft)]	1.97 (0.60)
DC-resistance outer conductor	[Ω/km (Ω/1000ft)]	4.84 (1.48)
Outer Conductor Material	Overlapping Copper Foil	
Inner Conductor Material	Copper Clad Aluminum Wire	
Diameter over Jacket	[mm (in)]	14.7 (0.58)
Diameter Outer Conductor	[mm (in)]	11.4 (0.45)
Diameter Inner Conductor	[mm (in)]	4.4 (0.17)
Minimum Bending Radius, Single Bend	[mm (in)]	200 (7.9)
Cable Weight	[kg/m (lb/ft)]	0.23 (0.16)
Max. tensile force	[N (lb)]	1300 (292)
Indication of Slot Alignment	Bulge atop slots	
Storage temperature	[°C (°F)]	-70 to +85 (-94 to +185)
Installation temperature	[°C (°F)]	-25 to +60 (-13 to +140)
Operation temperature	[°C (°F)]	-40 to +85 (-40 to +185)
Stop bands	[MHz]	None
Recommended / maximum clamp spacing	[m (ft)]	0.5 (1.6)
Minimum Distance to Wall	[mm (in)]	50 (2)
Length	[m (ft)]	

Notes

- Coupling loss as well as longitudinal attenuation of RADIAFLEX® cables are measured by the free space method according to IEC 61196-4.
- Coupling loss values are measured with a radial orientated dipole antenna.
- The coupling loss values given in brackets are average values of all three spatial orientations (radial, parallel and orthogonal) of dipole antenna.
- Coupling loss values are given with a tolerance of ±5 dB and longitudinal loss values with a tolerance of ±5%.
- As with any radiating cable, the performance in building or tunnel environments may deviate from figures based on free space method.
- Due to the cable design, single lengths should not be less than 80m (262ft).

Rev.

2013/10/15



ALF cable, A-series

PERFORMANCE			
Frequency, MHz	Longitudinal Loss, dB/100 m (dB/100 ft)	Coupling Loss 50%, dB	Coupling Loss 95%, dB
75	1,95 (0,59)	67 (70)	79 (82)
150	2,85 (0,87)	67 (70)	79 (82)
450	5,15 (1,57)	72 (75)	84 (87)
800	7,05 (2,15)	72 (75)	84 (87)
900	7,60 (2,32)	72 (75)	84 (87)
1800	10,95 (3,34)	77 (80)	89 (92)
1900	11,35 (3,46)	77 (80)	89 (92)
2000	11,70 (3,57)	77 (80)	89 (92)
2200	12,40 (3,78)	77 (80)	89 (92)
2400	12,95 (3,95)	77 (80)	89 (92)
2600	13,50 (4,11)	77 (80)	89 (92)

Standard conditions