




Coaxial Adapter 4.3-10 Male - 4.3-10 Male

Coaxial Adapter, 4.3-10 Male / 4.3-10 Male



Technical Features

STRUCTURE

Product Line	Coaxial Cable Components
Product Type	Coaxial Adapter
Coaxial Cable Type	Foam Dielectric, Ultraflexible Foam Dielectric , Radiating Cable

MECHANICAL SPECIFICATIONS

Connector A	4.3-10 Male
Center Contact Connector A	Copper Alloy, silver plated
Outer Contact Connector A	Copper Alloy, CuSnZn plated
Connector B	4.3-10 Male
Center Contact Connector B	Copper Alloy, silver plated
Outer Contact Connector B	Copper Alloy, CuSnZn plated
Dielectric	PTFE
Sealing class	IP68, connected

ELECTRICAL SPECIFICATIONS

Frequency Range	MHz	DC - 6000
VSWR, Return Loss	VSWR (dB)	DC TO 2GHz VSWR 1.02 : 1 MAX 2 TO 3GHz VSWR 1.04 : 1 MAX 3 TO 6GHz VSWR 1.08 : 1 MAX
3rd Order IM Product @ 2x20 Watts	dBc	< -166

PACKAGING INFORMATION

Package Quantity	1
------------------	---

External Document Links	Notes
--------------------------------	--------------