



Wall/Roof Feedthrough for SCF14, LCF14, SCF38, LCF38, HCA38, RG213, RGC213, RG214, RGC8, E220, E250, E300, E380

This innovative Wall feed through system feature a design which reduces installation time. The WFS-Kit contains a rubber wall gland which fit to the mounting plate to hold the waveguide or coaxial cable in place. It is fixed by a threaded jacket. The cable or waveguide sealing is done with a hot melting glue.

FEATURES / BENEFITS

Elliptical Waveguide installation

- ➔ The wall gland provides a single entry in conjunction with a feed through plate
- ➔ It consists of a inner part with thread, O-ring and hot shrink part



Technical Features

STRUCTURE

Product Line		Coaxial Cable Accessories
Product Type		Wall/Roof Feed-Through System
Feed-Through Component		Single Entry Kit
Transmission Line Type		SCF14, LCF14, SCF38, LCF38, HCA38, RG213, RGC213, RG214, RGC8E220, E250, E300, E380
Coaxial Cable Type		Foam Dielectric
Cable Size		1/4"

MECHANICAL SPECIFICATIONS

Feed-Through Holes		1
Feed-Through Hole Diameter	mm (in)	6.0 - 19.0 (0.24 - 0.75)
Color		Black
Length	mm (in)	70 (2.75)
Diameter	mm (in)	36 (1.41)
Drill Hole Size	mm (in)	25.5 (1)

PACKAGING INFORMATION

Package Quantity		1
-------------------------	--	---

External Document Links	Notes
-------------------------	-------