

## N Female Connector for 1/2" RADIAFLEX® cable

**Product Description**

These single-piece high performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to RADIAFLEX® cables. The connectors provide outstanding value to users because they permit quick, easy and reliable installation at any location, thereby allowing the operator flexibility while saving installation time and money. They attach to prepared cable in one piece assuring error-free attachment. All connectors are fully tested for mechanical and electrical compliance specifications. They are available in all popular cable sizes in both type N and 7-16 DIN interface.



RADIAFLEX connector

**Features/Benefits**

- Single-piece design for Fast and Easy Installation - Reliable and simple attachment avoids unnecessary connector adjustments and provides outstanding performance. Saves time and provides cost savings.
- Robust Mechanical Design - Low and consistent IM performance.
- Excellent Electrical Performance - Low VSWR
- Totally Waterproof - Assures safe, long term operation in the harshest of environments.

**Technical Specifications**

Transmission Line Type	Coaxial Cable
Cable Size	1/2"
Cable Type	Radiating
Model Series	all RLF and RLK12-50A-Series
Connector Interface	N
Nominal Impedance, ohms	50
Connector Type	Straight
Sealing Method	Shrinking Sleeve
Gender	Female
Length, mm (in)	70.8 (2.79)
Outer Diameter, mm (in)	26.8 (1.06)
Weight, kg (lb)	0.11 (0.24)
Body Material	Brass / Plating: Tri metal
Inner Contact Material	Copper / Plating: Silver
Inner Contact Attachment	Spring Finger / Plating: silver
Outer Contact Attachment	Spring loop / Plating: silver
Maximum Frequency, GHz	6.0
Waterproof Level	IP68

**Notes****Other Documentation**

Installation Instruction: [2800117-D\\_Inst Con\\_NM-RA12-011 and NF-RA12-012.pdf](#)

