N Female Connector for 1/2" Coaxial SuperFlexible Cable, OMNI FIT™ standard

Product Description

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications. The N connector is one of the most common RF connector types and meets all requirements even under the most severe environmental conditions.



OMNI FIT™ Standard Connectors

Features/Benefits

- Cost effective two-piece design for safe and easy installation
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up, reduces the number of dropped calls and avoids revenue losses
- Standard electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) compliant i.e. can be used on a global basis

Coaxial Cable	
1/2"	
Foam Dielectric, Superflexible	
SCF12-50 Series	
N	
50	
OMNI FIT™ Standard	
O-ring	
Female	
Trimetal/Silver	
50.4 (1.99)	
19.8 (0.78)	
0.06 (0.13)	
Basket	
Rigidity impaction	
-159 typical	
3.7	
0 < f = 1.0 GHz: 1.03 (36.6)	
1 /	
18 (7/10)	
IP68	
.	1/2" Foam Dielectric, Superflexible SCF12-50 Series N 50 OMNI FIT™ Standard O-ring Female Trimetal/Silver 50.4 (1.99) 19.8 (0.78) 0.06 (0.13) Basket Rigidity impaction -159 typical 3.7 0 < f = 1.0 GHz: 1.03 (36.6) 1.0 < f = 2.7 GHz: 1.04 (34.1) 2.7 < f = 3.7 GHz: 1.08 (28.3) 18 (7/10) 18 (7/10)

Notes

Other Documentation

Installation instruction: 10000006017-04.pdf

RFS

N Female Connector for 1/2" Coaxial SuperFlexible Cable, OMNI FIT™ standard

