

Pos	pcs.	TG part number	description	remarks
1	1	J01010F2255	TNC-Straight Plug, CR/CR, Standard	crimp/crimp
2	1	J01010F2255	TNC-Straight Plug, CR/CR, Standard	crimp/crimp
3	8000 mm	L01000A0003	RG-58 PVC	50 Ohm
4	1	B00081A1272	strain relief black	25 mm
5	1	B00081A1272	strain relief black	25 mm
6	0		labeling left	
7	0		labeling middle	
8	0		labeling right	
requested quantity: 1			order quantity:	

Technical Data:

cable:
 cable name: RG-58 PVC
 impedance: 50 Ohm
 total length: 8000 mm
 cable tolerance according to DIN 47101: 7985 mm ±100 mm
 cable cut length: 8085 mm -200 mm

type left:
 connector name: TNC-Straight Plug, CR/CR, Standard
 connector design: straight
 protection: strain relief black
 assembly construction code: A0205



type right:
 connector name: TNC-Straight Plug, CR/CR, Standard
 connector design: straight
 protection: strain relief black
 assembly construction code: A0205

quality check program number: L03200A0001

standard delivery form:
 Standard cables from 1 m length twisted into a ring with Ø 180 mm, doubly secured with a rubber band and packed in a transportable cardboard box. Testline cable twisted into a ring with Ø 280 mm and packed in a PE foil with test protocol.

For your information only! Coax Configurator is subject to technical verification!

To request or to order this configuration please contact your distributor or send this PDF to cableconf@telegaertner.com or call +49 (0)7157-1250.

2016	date	name			prod.order.no.
	07.09.2016	autom.			
scale	title				 Telegärtner
	RF - cable assembly				
dim. without tolerances according to	doc.type	ref.no.	L09999B8247		
			 dimensions: mm Original: DIN A4		