

RSB-Clip

Product Description

The RSB Clip RSB-78 is designed for the installation of CELLFLEX[®] foam-dielectric cables of 7/8" size. The clip is a universal clamp device and can be used in many mounting configurations. When replacing a cable the clip can be opened without any tools. After replacing the cable the clips are easily closed again. The RSB is the abbreviation of Rostfreier Stahl[®] and means stainless steel hanger. The hanger is resistant against all environmental influences. Due to its mechanical construction cable deformation is impossible and deterioration of the electrical properties is avoided.

**Features/Benefits****Technical Specifications**

Product Line	Coaxial Cable Accessories, Hybrid Cable Accessories
Product Type	Hanger
Hanger Type	RSB-Clip
Transmission Line Type	LCF78, UCF78, RLF78, RLFW78, RAY78, RAYB78, RLKW78, RLKU78, RCF78, HB012
Cable Type	Coaxial Foam Dielectric, Superflexible Coaxial Foam Dielectric, Ultraflexible Coaxial Foam Dielectric, Radiating Cable, Hybrid
Cable Size	7/8"
Number of Cable / Waveguide Runs	1
Spare Part / Useful Accessories	Cleat : RSB-310 Anchor bar fixation : RSB-315
Material	Stainless Steel
Installation Temperature, °C(°F)	-50 to 85 (-58 to 185)
Operation Temperature, °C(°F)	-50 to 85 (-58 to 185)
Storage Temperature, °C(°F)	-50 to 85 (-58 to 185)
Drill Hole Size, mm (in)	8 (0.315)
Package Quantity	10

Notes**Other Documentation**

Application Note RSB Clip: [AN 040511.pdf](#)