



Radio Frequency Systems line of high performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to CELLFLEX® coaxial cables. RFS connectors are fully tested for mechanical and electrical compliance specifications. They are available in all popular cable sizes in a variety of mating interfaces. The N connector is one of the most common RF connector types. N type connectors from RFS will be delivered with a non-slotted outer conductor contact sleeve and a special gasket. Due to a special design of the coupling nut (without spring ring) N connectors can be tightened with increased torque. This increases the contact pressure.

**FEATURES / BENEFITS**

- Single-piece design for Fast and Easy Installation - Reliable and simple attachment avoids unnecessary connector adjustments and provides outstanding performance every time. Saves time and provides cost savings.
- Robust Mechanical Design - Low and consistent intermodulation performance guarantees outstanding system sensitivity.
- Excellent Electrical Performance - Consistent and repeatable low VSWR improves overall system performance and margin and reduces mismatch losses
- Totally Waterproof according to IP 68 - Assures safe, long term operation in the harshest of environments.

**RAPID FIT™**



RAPIT FIT™ Connectors

**Technical features**

**GENERAL SPECIFICATIONS**

Transmission Line Type		Coaxial Cable
Cable Size		3/8
Cable Type		Foam Dielectric
Connector Interface		N
Connector Type		RAPID FIT™
Sealing Method		O-ring
Gender		Male

**ELECTRICAL SPECIFICATIONS**

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	
Maximum Frequency	GHz	3.7
VSWR, Return Loss	VSWR (dB)	0 <math>f \le 1.0 \text{ GHz}</math>: 1.02 (40) 1.0 <math>f \le 2.7 \text{ GHz}</math>: 1.03 (36.6) 2.7 <math>f \le 3.7 \text{ GHz}</math>: 1.08 (28.3)

**MECHANICAL SPECIFICATIONS**

Plating Outer/Inner		Silver/Silver
Length	mm (in)	53.1 (2.1)
Outer Diameter	mm (in)	22 (0.9)
Inner Contact Attachment		Basket
Outer Contact Attachment		Spring Finger


**ACCESSORIES**

Wrench size front	mm (in)	17 (11/16)
Wrench size rear	mm (in)	15 (9/16)
Trimming Tool		TRIM-38-L03



**TESTING AND ENVIRONMENTAL**

Waterproof Level		IP68
------------------	--	------



External Document Links

[Installation Instruction](#)

Notes