

Art.No. 10430012


Standard article

This article is available from stock, barring to unforeseen circumstances

EcoLine+

(T)ET-1-8+

1-way tap
1-way tap, 9dB



ET-1-8+



TET-1-8+



ModemSafe® integrated

	Port	Range	Min.	Typical	Max. Unit	Rem.	Margin
Frequency Range			5		1000 MHz		
Connectors	In/Out/Tap				F-female		
Equipment Approval					CE		
Insertion Loss	In -> Out	5 MHz < F < 40 MHz	1,0	1,4	1,8 dB		
		40 MHz < F < 470 MHz	0,8	1,2	1,6 dB		
		470 MHz < F < 862 MHz	1,2	1,6	2,0 dB		
		862 MHz < F < 1000 MHz	1,4	1,8	2,2 dB		
Tap Loss	In -> Tap	5 MHz < F < 40 MHz	7,0	8,5	10,0 dB		
		40 MHz < F < 1000 MHz	7,5	8,5	9,5 dB		
Return Loss	In/Out/Tap	5 MHz < F < 10 MHz	20		dB		
		10 MHz < F < 862 MHz	22		dB	1	
		862 MHz < F < 1000 MHz	14		dB		
Isolation	Out -> Tap	5 MHz < F < 10 MHz	22		dB		
		10 MHz < F < 862 MHz	27,5		dB	1	
		862 MHz < F < 1000 MHz	19,5		dB		
Screening Effectiveness	-	5 MHz < F < 300 MHz	85	95	dB	2	
		300 MHz < F < 470 MHz	80	90	dB	2	
		470 MHz < F < 1000 MHz	75	85	dB	2	
Intermodulation p+q (min)	All ports DC blocked				-115 dB	3	

Remarks:

- F > 40 MHz -1.5 dB/oct
- Transfer impedance method according IEC 60728-2 (5-30 MHz)
Absorption clamp method according IEC-60728-2 § 4.4 (30-1000 MHz)
- Two carriers (50 & 55MHz), out/ tap to in, @ 120dBµV, after 10 pulses (25V/1,2µS risetime/500µS duration) at all ports.

note: Specifications are measured at room temperature

PRELIMINARY SPECIFICATIONS. CHECK OUR SALES SUPPORT DEPARTMENT FOR POSSIBLE CHANGES

spec version: 01
print-date: 28-04-2004

10