

Electrical Characteristics


Nominal Impedance: 75 ohms
Frequency Range: DC to 2 GHz
Operating Voltage (rms): 500 V maximum at sea level
Dielectric Withstand Voltage (rms): 1500 V maximum at sea level
Contact Resistance: 3.0 milliohms maximum
Insulation Resistance: 5000 megohms minimum

Mechanical Characteristics

Mating Cycles: 500 cycles minimum

Environmental Characteristics

Temperature Range: -55 °C to +85 °C



PART	DESCRIPTION
1	Body
2	Dielectric
3	Dielectric
4	Contact

CAD Issue	SN	2	04 Sep 02
First Issue	PDC	1	09 Feb 01
DESCRIPTION OF REVISION	APPVD	ISS	DATE

TITLE:

Right Angle F Plug to F
Jack Adaptor

PART NUMBER:

VFA342

SCALE: Not To Scale

DIMENSIONS: mm

TOLERANCES:
± 0.2mm unless
otherwise stated

DRAWN BY:

S Nash

CHECKED BY:


P Couzens

APPROVED BY:

P Couzens

DATE:

04 Sep 02



EMERSON™

Network Power

Connectivity Solutions
7-13 Russel Way,
Widford Industrial Estate,
Chelmsford, Essex,
CM1 3AA, UK.
Tel: +44 (0) 1245 359515
Fax: +44 (0) 1245 358938