

## XPOL panel antenna 120°, 11 dBi, 380 - 470 MHz

### DESCRIPTION

- The 760/766 series of UHF Panel antenna has been designed for TETRA / UHF Trunked Radio applications, offering a stable performance an PIM specification over a wide bandwidth.
- available in VPOL and XPOL formats, the main housing of the antenna is made from corrosion resistant marine grade aluminium.
- The antennas compact design gives very low wind loading characteristics, and combined with the low weight of the antenna, aids in the reduction of structural loading.
- Former Skymasts brand product.




### SPECIFICATIONS

Electrical	
Model	766.12.11.00
Frequency	380 - 470 MHz
Max. Input Power	2 x 400 W
Polarisation	±45°
3 dB Beamwidth, E-Plane	18° ± 2°
3 dB Beamwidth, H-Plane	115° ± 5°
Impedance	50 Ω
Gain	8.9 dBd (11 dBi)
Port-Port Isolation	≥ 27dB
VSWR	< 1.5:1
Front-To-Back Ratio	> 20 dB
Cross Polar Discrimination	30 dB
Passive Intermodulation	-153 dBc (3rd Order, 2 x Tx @ 43 dBm)
Antistatic Protection	All metal parts DC-grounded (Connector shows a DC-short)
Mechanical	
Connection(s)	2 x 7/16(f)
Housing Material	Aluminium Alloy, Marine Grade 5083
Radome Material / Colour	White ASA, UV Resistant
Dimensions	1840 x 300 x 216 mm
Wind Load	445 N (160 km/h)
Weight	Approx. 11 kg / 24.25 lb.
Alternate Mounting Bracket	Tilt bracket : 766.7010 (0 - 12°) 766.7020 (0 - 22°) (Ordered Separately)
Environmental	
Operating temperature range	-40 °C to +75 °C
Survival Wind Speed	270 km/h
Ingress Protection	IP56

### ORDERING


Model	Product No.	Description	Frequency
XPOL panel antenna 120°, 11 dBi	766.12.11.00	7/16(f) termination	380 - 470 MHz
XPOL panel antenna 120°, 11 dBi	766.12.11.00-N	N(f) termination (not PIM specified)	380 - 470 MHz
Accessories			
Bracket kit for 760/766 panel (large), 0-12°	766.7010		

### RADIATION PATTERNS



E-Plane | 425 MHz

### RADIATION PATTERNS



H-Plane | 425 MHz